

## Model 2025D 25 KVA CORE LOSS TESTER

The Model 2025D Core Loss Tester is a fully automated high current, low voltage test center designed specifically for testing rotors, stators, and armatures up to 1250 HP or 25kVA. The Model 2025D simulates the real-world operating conditions and calculates core loss based on actual device characteristics using our industry-leading MP6.0™ software. The Model 2025D provides documentation of the rebuild and manufacturing processes by automatically generating customized reports detailing core performance.

The Model 2025D Core Loss Tester verifies the effectiveness of the repair and production processes therefore protecting against premature motor failures. This verification assures greater reliability and efficiency while reducing warranty costs and improving customer satisfaction.

The LEXSECO Model 2025D Core Loss Tester provides a quick, efficient, and highly accurate method for determining losses found in the core of stators, rotors, and armatures. Core loss is a major cause of inefficiency in electric motors, second only to copper winding loss. The LEXSECO Core Loss Tester can determine if a motor is capable of operating at rated efficiency after rebuilding or at time of manufacture and provides the highest accuracy available today.

The LEXSECO automated Core Loss Testers assure that electric motor products are reliable and energy efficient. This assurance shows that you are protecting your customers' investment by reducing downtime and energy consumption and reducing your costs associated with warranty repairs.



### Key Features

- Fully automated test process
- Flux Measurement accuracy of  $\pm 0.1\%$  per range
- MP6.0™ software
- Measurement system specifically designed for core loss testing
- NIST compliant & certified calibration process
- Winding verification
- Complete repair documentation center
- 230 VAC—575 VAC, 50 and 60 Hz models
- Thermal overload protection
- Rugged steel cabinet with locking lid
- Locking casters
- DC Armature & AC Rotor Testing Package available



## Model 2025D 25 KVA CORE LOSS TESTER

**LEXSECO'S Software is the Standard**

Exceptionally versatile and user friendly, the industry leading MP6.0™ differentiates between NEMA, pre-NEMA, U, T and IEC frames and standard and high efficiencies and applies the appropriate specification limits to the test. Users may also build their own databases with special parameters for the particular equipment they service or manufacture. Also, MP6.0™ contains a Winding Verification program and an array of customizable mechanical and electrical testing fields that enables our Core Loss Tester to be a powerful repair documentation center.

LEXSECO developed the first standardized core loss parameters representing the appropriate average of the existing data from motors found in the marketplace. LEXSECO soon realized that acceptable losses varied with core configuration. Separate parameters need to be determined for each frame and efficiency type in order to achieve the greatest accuracy. This discovery led to the development of the MP6.0™ software.

MODEL 2025D TECHNICAL SPECIFICATIONS	
Test Capacity	1250 HP maximum
	25 KVA maximum
Input	460VAC / 60A
Dimensions W x D x H	24" x 39" x 48" (69" with lid open) 610mm x 991mm x 1219mm (1752mm with lid open)
Weight	845lb (384kg)

PART NUMBERS	
L30025	Model 2025D Core Loss Tester, 460-575VAC, 50/60Hz, Single phase
L30025-0	Model 2025D Core Loss Tester, 460VAC, 60A, 60Hz
L30025-1	Model 2025D Core Loss Tester, 575VAC, 60A, 60Hz
L30025-2	Model 2025D Core Loss Tester, 240VAC, 120A, 60Hz
L30025-3	Model 2025D Core Loss Tester, 400VAC, 60A, 50Hz
L30025-4	Model 2025D Core Loss Tester, 230VAC, 120A, 50Hz
	Please request a quote for voltages not listed.
L00500	DC Armature & AC Rotor Testing Package (includes additional cable, shaft clamps & fittings)
L10002	Computer & Printer kit with factory installed MP6.0™ software and meter data retrieval system

USA Headquarters: Telephone: (1) 502 366 0916 Fax: (1) 502 238 1001  
 IRD LLC 4740 Allmond Ave. Louisville, KY 40209, USA  
 UK: Telephone: +44 1244 538170 Fax: +44 1244 528900  
 IRD UK Ltd. International House, Aviation Park, Flint Road, Saltney Ferry, Chester UK CH4 0GZ  
 MEXICO: Telephone: +52.55.5689.8325 Fax: +52 55.5689.8160  
 IRD Balancing México S. de R. L. de C.V.; Miguel G. Kramer #29, Col. Atlántida Del. Coyoacán, México, D. F.C.P. 04370  
 CANADA: Telephone: 1.450.724.4066 Fax: 1.450.724.4077  
 IRD Canada Ltd. 755 Jean-Baptiste-Varin, La Prairie, QC J5R 6P3, Canada

Specifications are subject to change without prior notice.

Copyright © 2009 IRD®  
 All rights reserved.

Publication No: E51282

Email: [sales@lexseco.com](mailto:sales@lexseco.com)

[www.lexseco.com](http://www.lexseco.com)

[www.lexseco.com](http://www.lexseco.com)